

Hillmar

Hillmar Industries Ltd.

7371 Vantage Way
Delta, BC V4G 1C9
P:604 946-7115 F:604 946-0329
info@hillmar.com www.hillmar.com

SPOO SRGA
SRGA-GB12-800-2200-16
SPECIFICATION SHEET
SLS & MKTG
ENGLISH

Sheet Number:

Job Number:

Form Number:

629-811-35815PT

Company / Project Reference:

Date.:




Page.:

1 OF 1

Document Package No.:

Rev.:

Inventor Drawing



FEATURE	CODE
Spool Round Galvanized	SRGA
Gearbox Size	GB12
Inside Diameter (mm)	800
Outside Diameter (mm)	2200
Spoke Quantity	16

Example for ordering	SRGA-GB12-800-2200-16
----------------------	-----------------------

TECHNICAL DATA

Weight of Spool (kg)	82
Spoke H x W x T	38 x 25 x 3
Spool Gap (mm) C	* JOB SPECIFIC
Spool Width (mm)	C + (2 x W)
Mounting Holes	8 x Ø22
Mounting Bolts	8 x M20 x 70 DIN 931-10.9 DAC

NOMINAL SPECIFICATION

Spools are manufactured from standard components to form a modular bolted assembly.

This product is used for round cable.

All structural fasteners are plated Gr. 10.9 bolts and all small non-structural fasteners are 304 stainless steel.

Stainless steel construction can be supplied

but only as a special option.

NOTES

Hillmar Spools can be customized to suit customer cable requirements.

All dimensions are in millimeters.

All figures given are nominal figures only.

Document Template #710-101-62058

** ALL TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE **

Hillmar works have a fully registered ISO 9001-2008 quality assurance programme (QCB #01-1525)

Storm Brakes • Thruster Disc Brakes • Thruster • Industrial Disc Brakes • Hydraulic Power Units • Cable Reels

C:\TEMP\7421e19-5451-4a98-a399-916f534e8370\80000524073\HILLMAR\HILLMAR PRODUCTION\06 CABLE REEL\SPools\0700-607006001 SGF-SGRISPC-SHT-SGF-SGRROUND\35815 SRGA-GB12-800-2200-16.dwg